

PRODUCT



1.75m MINI SHOCK LANYARD

Code: 1.75MMINISHOCKCR

DESCRIPTION

STL 1.75M Mini Shock Lanyard.

Light Weight durable shock absorbing lanyard designed for use in all sectors. Offering a Fall Factor 2, 140kg max user weight along with Technora Covered 32 braid high strength rope which provides increased resistance to cutting rope and high heat resistance. A double action Black snap hook and wear protection sleeve with integrated tie back loop complete the assembly.

FEATURES

- Heat Resistant Rope Core, Nylon Cover, Technora® Braid, 32. High decomposition point (up to 500°C) High strength Increased Resistance to Cutting and Abrasion.
- Light Weight Mini Shock Absorber Rated to Fall factor 2, 140kg.
- Protective Sleeve to minimis wear on the rope fitted with ring to allow for chocking on poles.
- Double Action Black Snap Hook

MATERIALS

Item 1: 11mm Alloy Triple Lock Carabineer

Item 2: Energy Absorber with progressive tear, Protected by a strong zip-case.

Item 3: Aluminium Multi-directional gated ring

Item 4: Heat Resistant, Cut Resistant Rope

Item 5: double action Black snap hook

CONFORMITY

Item 1: EN 362

Item 2: EN 355:2002 Fall factor 2 140KG

Item 3: CE EN 362

Item 4: EN 1891A

Item 5: EN362:2004/T



Safety Technology Limited © 2014

The Stone Barn, Lower Ty-Newydd, Clytha, Raglan, Monmouthshire, NP15 2BQ
T: +44 (0)1873 840 036 E: info@safetytechnology.co.uk W: www.safetytechnology.co.uk